

Cap termostatic de reglare / Regulation thermostatic head  
 Presiune maxima statica de lucru / Max static working pressure: 10 bar  
 Temperatura maxima de lucru / Max working temperature: 120°C  
 Presiune maxima diferentiala / Max differential pressure: 1 bar  
 Interval de reglare /Regulating range: 20-65°C  
 Lungime capilar / Capillary lenght: 2m

Presiune maxima de functionare / Max working pressure: 10 BAR  
 Presiune minima de functionare / Min working pressure: 0.1 BAR  
 Temperatura maxima la intrare / Max working temperature: 90°C

Termostat de siguranta / Safety thermostat  
 Setare fabrica / Default set: 55°C  
 Contact / Contac: Normal inchis / Normal closed  
 Grad de protectie / Protection: IP67  
 Temperatura maxima / Max temperature: 150°C

Sensor la distanta cap termostatat / Thermostat head sensor

Model pompa / Circulator model: Wilo Para 25/7 SC  
 Alimentare electrica / Power supply: 230V +10%/-15%, 50/60Hz  
 Distanța între axe / Centre distance: 130 mm  
 Prinderi cu filet / Connection: G1"1/2  
 Temperatura de folosire / Temperature range: 0-95°C  
 Presiune maxima de folosire / Max working pressure: PN10

